

AERODROME CHART - ICAO


ARP 553034N 0043540W

AD ELEV 65FT

PRESTWICK EGPK

GUND (Geoid Undulation) = The height of the Geoid (MSL) above the Reference Ellipsoid (WGS 84) at the stated position.	
BEARINGS ARE MAGNETIC ELEVATIONS AND HEIGHTS ARE IN FEET	
ELEVATIONS IN FEET AMSL	138
HEIGHTS IN FEET ABOVE AD	(73)

RUNWAY/TAXIWAY/APRON PHYSICAL CHARACTERISTICS			
APRON / RWY / TWY	SURFACE	BEARING STRENGTH	ELEVATION
RWY 13/31	Concrete/Asphalt	113/R/C/W/T	-
RWY 03/21	Asphalt	70/F/C/X/U	-
Aprons A, B	Concrete/Asphalt	100/R/C/W/T	30ft amsl
Aprons C, F, H	Concrete/Asphalt	50/F/C/Y/T	-
Aprons G	Concrete/Asphalt	30/F/C/Z/T	-
Taxiways R, J	Concrete/Asphalt	65/R/C/W/T	-
Taxiway S	Asphalt	60/F/C/X/U	-



COM		
ATIS	121.125	PRESTWICK INFO
TWR	118.150, 127.150	PRESTWICK TOWER
	121.600	PRESTWICK FIRE
LIGHTING		
APCH 13	853m HI coded C/L with 5 bars.	
APCH 31	890m HI coded C/L with 5 bars.	
APCH 21	420m HI C/L 1 crossbar.	
THR 13/31	HI green with green W bars.	
THR 03	HI green with green W bars.	
THR 21	HI green with green W bars.	
RWY 13/31	Elev HI bi-d with LI omni-d component. HI colour coded C/L HI colour coded C/L. End lights red.	
RWY 03/21	HI bi-d. LI omni-d component. End lights red.	
TWY	Green C/L serving 13/31. (except Block 21 at Hold Q). Blue edge.	

CHANGE: LIGHTING AMENDED.

AERO INFO DATE 12 JUL 10